

### REF.3450 DUOX PLUS ILOFT TELEPHONE



The iLOFT telephone is a compact and extra slim door entry system that works in hands-free communication with the outdoor panel. Configurable in Push-to-talk mode if needed for very noisy surroundings. The integrated digital audio DUOX PLUS technology (2 non-polarized wires) ensures a high quality, hands-free communication without interferences. Sequential volume control with a sliding wheel. Equipment manufactured in ABS plastic with ultraviolet protection and elegant matt finish for easy cleaning. Surface installation.

#### BUTTONS

-  Button to activate/deactivate the communication with the door entry panel.
-  Door opener button and call to guard (if any, press when in standby).
-  Button to activate additional functions: stair light switching, 2<sup>nd</sup> door opening, panic call, etc.

### ACCESSORIES



Ref.5636



Ref.3388



Ref.3389

#### -DESKTOP

Fermax desktop support allows a call from the entrance panel to be answered from the office desktop. Recommended for offices, businesses and professionals who work from home.

5636 ILOFT TELEPHONE DESKTOP SUPPORT

#### -REPLACEMENT

3388 UNIVERSAL FRAME 120X240

3389 UNIVERSAL LARGE FRAME 210X240

GENERAL CHARACTERISTICS	3450
Technology	DUOX PLUS (non-polarized 2 wire full digital system)
Audio/Video system	Audio
Set-up (Installation)	Surface mounted
Handset with magnet to facilitate the hang up	-
Hands-free communication	Yes
Press-to-talk communication configurable	Yes
Induction loop	-
Color of the product	Matt white
Number of pushbuttons	3
Kind of pushbuttons	Mechanical
Number of leds for lighted indications	3 (red, blue and green)
PROGRAMMING OF THE TERMINAL ADDRESS	
From the terminal	-
From the outdoor panel or guard unit	Yes
From the outdoor panel throughout the apartment door bell	Yes
FEATURES	
Guard unit call	Yes (by means of the door release button when in standby)
Auto-on	Yes (only with panel nº 0 of its own block)
Additional function F1	Yes (Button F1 sends a negative and/or command)
Additional function F2	-
Apartment door bell differentiated from the outdoor panel	Yes
Connection for additional devices (call extension, light/buzzer activator, etc.)	Yes (ref. 2040, ref. 2438. Ref. 3467)
Doormatic (automatic door release for offices, etc.)	Yes (Green led indication)
ADJUSTMENTS	
Ring tones selection	Yes (5)
Call volume control	Yes (by sliding wheel)
Do-not-disturb mode	Yes (by sliding wheel) + red led indication
Audio volume control	Yes (by sliding wheel)
TECHNICAL FEATURES	
Product dimensions (width x height x depth) mm	90 x 146,5 x 20
Time to answer or open the door since the call is done	30 s.
Conversation time	90 s.
Conversation privacy	Yes
Voltage	18-24 Vdc
Maximum consumption	3.6 W
Standby consumption	0.4 W
Working temperature (°C)	[-5°C, +40°C]
Humidity	[0%, 90%]
Product Weight (kg)	0,16
Line adaptor included in the terminal	Yes (A, C, default position OFF)
Connections	Bin, Bin, Bout, Bout, -, A+, F1, T