

Product Code

F01421

## 1/W 4,3" WAY SLIM VIDEO KIT



Reference

1421

EAN

8424299014210

### Description.

#### Description

With the WAY SLIM KITS, FERMAX offers you the most practical and accessible way to enter in the home. WAY SLIM KITS are the extra slim video door entry kits with 2 wires for individual residences, allowing an intuitive use and featuring lots of functionalities.

Indoors The WAY SLIM monitor is a device of reduced dimensions and extra slim design, perfect to fit into any space at home. With an elegant white design, it inspires freshness and it offers a lots of functionalities. With a 4,3" colour capacitive touchscreen, you will manage all WAY functionalities. The monitor incorporates two pushbuttons to establish communication with the outdoor panel and to open the door, which incorporate Braille marking. Hands-free communication. From its capacitive touchscreen you can access to the OSD MENU and manage the monitor in an intuitive way.

Outdoors A WAY panel of 39mm thickness made of zamak with a wide angle CCD colour camera. Incorporates a light sensor, a hood for rain protection and a backlighted cardholder. Surface installation. With power supply included in the kit, it is possible to connect up to a 12Vdc 250mA lock release.

#### Technical Details

Technology: **2-wire non-polarized**

The kit includes:

- Panel with visor.

- 4,3" TFT color monitor with capacitive touch screen.
- Power supply.

**Features:**

- Intercom: It establishes communication between the monitors installed inside the house.
- Player: After 3 seconds, the monitor automatically records a video (in case there is a micro SD card installed) or a photo of the visits. You also have the option to manually take a photo while answering the call. Videos / photos recorded from the entrance panel are displayed on the monitor screen.
- Settings: Brightness / contrast, melody selection, date and time, day and night call volume, language selection (16 languages), etc.
- "Do not disturb" function: 1 hour, 8 hours or permanently.
- Call log: All calls both from the board to the monitor, from the monitor to the board and between monitors, are recorded and can be reviewed later.
- Capacitive touch screen: TFT 4,3" color digital monitor with capacitive touch screen that allows intuitive use.
- Visor: Protects the entrance panel from rain, snow, etc. Included in kit.

**Monitor Specifications:**

- Power supply for the monitor: DC 24 ~ 28V.
- Power consumption: Standby 12mA; 350mA operation.
- Monitor screen: 4,3" digital color TFT. Capacitive screen.
- Video signal: 1 Vpp, 75Ω, CCIR standard.
- Wiring: 2-wire, non-polarized.
- Dimensions: 225 (H) x 131 (V) x 18 (P) mm.
- Operating temperature: [-20°C, +55°C]

**Entrance Panel Specifications:**

- Made of Zamak.
- Backlit card holders.
- Visor for surface mounting.
- High sensitivity color CCD camera.
- Light sensor.
- Control of a relay to activate a lock release.
- Measurements: 95 (H) x 155 (V) x 25 (P) mm.
- With the power supply included in the kit you can connect a 12Vdc 250mA door opener.
- IP43
- Operating temperature: [-25°C, +70°C]

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system
155 x 95 x 39	2.386	23,4x29,5x11	Technologie WAY

Manuals

- 970022c\_Kit\_way\_SLIM\_V01\_22.pdf

Declaration of conformity

- DOCF01421EN.pdf

Products included



F01410

WAY KIT P.S.U. DIN4 24VDC-1.5A



F01416

1/W COLOUR WAY VIDEO KIT PANEL



F01425

4,3" SLIM WAY MONITOR 1

Accessories



F01418

WAY RELAY MODULE



F01419

WAY SWITCHER/DISTRIBUTOR



F01426

4,3" SLIM WAY MONITOR 2

Other images

