



Product Code

F01688

MARINE SIP PANEL ST3 AVP103 DDA

Reference	EAN
1688	8424299016887

Description.

Description

Marine SIP panel with 3 buttons. MARINE is the Fermax IP65 IK09 vandal-resistant plate. It is made of 2.5mm thick stainless steel. AISI 316L steel type.

Marine is the perfect choice to install in places with extreme weather conditions or in dangerous environments, humid or corrosive climates.

Steel color. Also available in color or with laser screen printing. See reference 31722 Marine SIP Elite plate.

The **call buttons** are vandal-resistant, made of stainless steel and with an anti-lock system, they resist any impact.

They include a card holder to house an information label. Marine plates do not include the recessed box or surface, they must be ordered separately. The surface plates include a protective visor.

- Configuration via webserver
- Programmable button for sequential P2P calls to up to 8 different terminals

- Possibility of connection to up to two VoIP switchboards, local or remote
- Compatible with MEET devices and MEET ME APP*

*For SIP integrations with MEET devices and/or MEET ME call forwarding, consult the possibilities in the installer manual. MEET ME license ref. 1496 call forwarding to mobile is purchased separately.

One to one module

The OneToOne module shows, using 4 LED icons, the status of the board.

These icons symbolize:

- Call
- Conversation
- Door Opening
- Busy channel.

NOTE: The "Channel Busy" icon is only displayed by the VDS System.

Protocols	SIP v1 (RFC2543), SIP v2 (RFC3261) over TCP, UDP or TLS RTP/RTCP/SRTP STUN DHCP SNTP FTP/TFTP HTTP/HTTPS TR-069
Audio	Codecs G.711A/U, G.729A/B, iLBC, G.723.1, G.726-32K, G.722, Opus DTMF In-band, Out-band (RFC2833/SIP INFO)
Outputs	2x CN/O relay, N/C maximum 30V/2A DC, 125V/0.5A AC
Network	Ethernet 10/100Mbps IPv4, IPv6, IPv4+IPv6 modes Static, Dynamic, PPoE IP Address L2TP VPN, OpenVPN VLAN
Supply	PoE Class 3 (30W max) 12-24Vdc/1A

<p>Others</p>	<p>Operating temperature: -30°C to 60°C Operating humidity: up to 95%, non-condensing Tested according to IEC 60068-2 standard</p>
----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------

Details.

Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
37x16,4x8,2	SIP

Manuals

- 970300Ab SIP marine panel installer manual v09_24.pdf
- 970300Eb Manual instalador Placa SIP Marine v09_24.pdf
- 970300Fb SIP marine panel installer manual v09_24.pdf
- 970300Ib SIP marine panel installer manual v09_24.pdf
- 970300Ob SIP marine panel installer manual v09_24.pdf
- 970300Pb SIP marine panel installer manual v09_24.pdf
- 970300Yb SIP marine panel installer manual v09_24.pdf
- 970318 Guia rapida Placa SIP Marine DDA V06_24.pdf
- 97737_Limpieza_Placas_Marine_V04_20.pdf


Accessories



F04643
MARINE ST3 FLUSH BOX



F04647
MARINE ST3 SURFACE BOX



F01496
MEETME CALL DIVERT LICENSE W/O TERM 1APT



F04813
P.S.U. DIN6 100-240VAC/12VDC-2A



F01586
SWITCH POE 4 PORTS



F01587
SWITCH POE 8 PORTS