

Product Code

F01728

## ELECTRIC STRIKE 540Aa-412 MAX

Reference

1728

EAN

8424299017280

## Description.

## Description

**Reversible (Right DIN or Left DIN).**

Lets you open the door from right and left.

**Symmetrical.**

Allows to change hands, maintaining the body symmetry.

**DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

-If the hinges are on the observer's right, it is a right DIN.

**Max Adjustable Latch:**

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

**Operating type.**

There are several types of door lock release mechanisms depending on the type of operation needed.

**Aa-412 Automatic Invisible type 12Vdc** (Invisible Automatic Operation and 12 Vdc activation). The door release is automatically unlocked when it receives a 12Vdc voltage pulse. The lock release is blocked again once the voltage is cut off and the door opens and closes again mechanically. It is designated invisible because it does not have the normal automatic lock pin.

## Technical Details

**Consumos:**

N, A 12Vac: 560mA

N-412 12Vdc: 260mA.

N-424 24Vdc: 180mA.

N-512 12Vdc: 200mA.

N-524 12Vdc: 120mA.

Dimensiones:

Serie 540, 67(V)mmx20,5(H)mmx28(P)mm

MAX Pestillo ajustable: 3mm

Details.

---

Weight (kg)	Packaging measurements	Video Door Entry system
0.165	(height x width x depth) cm	Technologie
	2,7x10,2x3,2	GENERICA