



Product Code

F01779

ELECTRIC STRIKE 540AD MAX

Reference

1779

EAN

8424299017792

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

Type A Automatic 12Vac (Automatic operation and 12 Vac activation).

The lock release is unblocked when it receives a 12Vac voltage pulse. The lock release is blocked again once the voltage is cut off and the door opens and closes again mechanically. For proper installation, the automatic lock pin must be pressed in 3mm by the latch once the door is closed again.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

-If the hinges are on the observer's right, it is a right DIN.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

Technical Details

Consumos:

N, A 12Vac: 560mA

N-412 12Vdc: 260mA.

N-424 24Vdc: 180mA.

N-512 12Vdc: 200mA.

N-524 12Vdc: 120mA.

Dimensiones:

Serie 540, 67(V)mmx20,5(H)mmx28(P)mm

MAX Pestillo ajustable: 3mm

Details.

Weight (kg)

0.1675

Packaging measurements

(height x width x depth) cm

2,7x10,2x3,2

Video Door Entry system

Technologie

GENERICA