



Product Code

F01782

# ELECTRIC STRIKE 540N-412 MAX

Reference

1782

EAN

8424299017822

## Description.

---

Description

### Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

### N-412 Normal type 12Vdc (Normal operation and 12 Vdc activation).

The lock release is unblocked for the time that the 12 Vdc voltage is applied.

### Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

### Symmetrical.

Allows to change hands, maintaining the body symmetry.

### DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

- If the hinges are on the observer's right, it is a right DIN.

**Max Adjustable Latch:**

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

Technical Details

**Consumption:**

- N, At 12Vac: 560mA
- N-412 12Vdc: 260mA.
- N-424 24Vdc: 180mA.
- N-512 12Vdc: 200mA.
- N-524 12Vdc: 120mA.

**Dimensions:**

- 540 series, 67(V)mmx20.5(H)mmx28(P)mm

**MAX Adjustable Latch:** 3mm

Details.

---

|             |                             |                         |
|-------------|-----------------------------|-------------------------|
| Weight (kg) | Packaging measurements      | Video Door Entry system |
| 0.164       | (height x width x depth) cm | Technologie             |
|             | 2,7x10,2x3,2                | GENERICA                |