



Product Code

F01782

## ELECTRIC STRIKE 540N-412 MAX

Reference

1782

EAN

8424299017822

### Description.

---

Description

#### Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

**N-412 Normal type 12Vdc** (Normal operation and 12 Vdc activation).

The lock release is unblocked for the time that the 12 Vdc voltage is applied.

**Reversible (Right DIN or Left DIN).**

Lets you open the door from right and left.

**Symmetrical.**

Allows to change hands, maintaining the body symmetry.

**DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

-If the hinges are on the observer’s right, it is a right DIN.

**Max Adjustable Latch:**

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

Technical Details

**Consumos:**

- N, A 12Vac: 560mA
- N-412 12Vdc: 260mA.
- N-424 24Vdc: 180mA.
- N-512 12Vdc: 200mA.
  
- N-524 12Vdc: 120mA.

**Dimensiones:**

Serie 540, 67(V)mmx20,5(H)mmx28(P)mm

**MAX Pestillo adjustable:** 3mm

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.164	(height x width x depth) cm	Technologie
	2,7x10,2x3,2	GENERICA