



Product Code

F01817

## UNIVERSAL ELECTRIC STRIKE 990N-L22 10-24V MAX

Reference

1817

EAN

8424299018171

### Description.

---

#### Description

**Reversible (Right DIN or Left DIN).**

Lets you open the door from right and left.

**Symmetrical.**

Allows to change hands, maintaining the body symmetry.

**DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

**Max Adjustable Latch:**

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

**Flush mounted Door lock.**

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted. **D Unblocking**

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

**Type L22 flush shield.**

For doors with deadbolt entry.

L22 type metallic trim fitted with an electrical mechanism to form a flush-fit lock release. Slightly narrower than standard width, recommended for smaller-sized aluminium and PVC frames.

**Dimensions: 22(H)x250(V)mm.**

Details.

---

Weight (kg)	Packaging measurements	Video Door Entry system
0.2109	(height x width x depth) cm	Technologie
	3,4x25x2,7	GENERICA