



Product Code

F02013

ADDITIONAL FUNCTIONS RELAY

Reference	EAN
2013	8424299020136

Description.

Description

Small size allows installation in electrical cabinets. Can be flush-fit in standard boxes 10x10 cm. With adhesive strips for fixing, or may be screwed directly onto the wall. Necessary to activate an external device (courtesy light, second door, etc) from the corresponding button (additional button) located in the phone or monitor.

Technical Details

- Maximum operations/second: 20
- Feeding:
 - Terminals "+18V" and "3" = +18 Vdc
 - Terminals "3" and "4" = 8 - 12 Vdc / Vac
- Consumption:
 - Sleep: 0 mA - Active: 70 mA
- Operating temperature:
 - -30°C +65°C,
 - RH 90% without condensation
- Dimensions:
 - 61.3 x 68.6 x 20.4 mm (HxWxD)
- Contacts:

- Maximum switchable voltage:
 - 220 Vac (1 A)
 - 36 Vdc (2 A)
- Dimensions: 62x70x20 mm ((height-width-depth)).

Details.

Weight (kg)

0.05508

Packaging measurements

(height x width x depth) cm

6,3x2,4x9

Video Door Entry system

Technologie

GENERICA

Manuals

- 94457c Rele 2013
V07_08.pdf

Declaration of conformity

- DOCF02013EN.pdf