



Product Code

F02409

VDS/MDS DECODER

Reference

2409

EAN

8424299024097

Description.

Description

MDS-VDS system: Installations with MDS system in general entrances and interior blocks with audio/video door entry and/or VDS detached homes.

One MDS/VDS decoder is required per block. The MDS/VDS decoder converts the general entrance MDS system to the VDS system in the interior blocks.

The MDS/VDS decoder can handle 1 to 199 homes per block. From the MDS general entrance, communication can be enabled with any home in the different blocks.

Wiring

MDS

- Audio: 6 wire BUS
- Video: audio bus + Coaxial (video) + 2 power supply wires
- Maximum distance in the installation depending on cable section used (please consult technical guides)

VDS

- Audio: 3-wire bus.
- Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).
- Maximum distance from first access to last home: 200 m.

Small size allows installation in electrical cabinets. Can be flush-fit in standard boxes 10x10 cm. With adhesive strips for fixing, or

may be screwed directly onto the wall. The MDS/ADS decoder carries out conversion of the general entrance MDS system to the ADS system in the interior blocks. One MDS/ADS decoder is required per block. The MDS/ADS decoder can handle 1 to 199 homes per block. From the MDS general entrance, MDS communication can be enabled with any home in the different blocks. In addition to interfacing between the two systems, the MDS/ADS decoder acts as an audio switcher, which in standby (without communication with a general entrance or MDS guard unit) lets you establish communication between ADS indoor panels and the homes in the corresponding block. In this way it is possible to hold simultaneous conversations in different blocks, each with its indoor panel, in addition to a block with general entrance. Decoder installation should preferably be done where the inner block power supply is fitted, next to the video switcher if there is one. It is very important to use a power supply for each interior block to avoid interference with the signals generated in a block (calls, call confirmation tones, etc).

Technical Details

Dimensions: 62x85x20 mm (height-width-depth).

MDS power supply:

- Audio: 12 Vdc
- Video: 18 Vdc

ADS power supply:

- Audio and Video: 18 Vdc

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
0.1084384	6,4x11,9x7,4	MDS

Manuals

- 97651Ab Man avanzado Decoder VDS 2409 V01_12.pdf
- 97651Eb Man avanzado Decoder VDS 2409 V01_12.pdf
- 97651Fb Man avanzado Decoder VDS 2409 V01_12.pdf
- 97651Ib Man avanzado Decoder VDS 2409 V01_12.pdf
- 97674 Decoder VDS 2409 V01_12.pdf
- 97708 Cambio-Selección de modo Decoder VDS V01_13.pdf

Declaration of conformity

- DOCF02409EN.pdf