



Product Code

F02536

VDS CITYMAX GUARD UNIT

Reference

2536

EAN

8424299025360

Description.

Description

The new CityMax guard unit has a 4" screen, dialling keypad (located under the phone handset) and fast access function buttons for easy and convenient facility and guard unit management.

Extra flat format, made in high impact ABS plastic and with a mirror polish type finish for easy cleaning.
Includes desktop support. Allows surface installation.

Basically, the Central Guard Unit acts as "filter" between the visitors to a building and its residents. During normal operation, the calls made from any outdoor access panel to the building are received in the Central Guard Unit, which can announce the visit to the corresponding resident, pass on the call, or deal with it personally. The guard unit, through its built-in display, informs on all incidents and actions in the facility: call source, call type, call in progress, calls waiting, latest communication, etc. The guard unit has several operating modes. The guard unit can communicate with any access (outdoor panel) or home.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video). Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit. Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

Technical Details

- Search keys: Let you look for the name of the resident you wish to call.
- Call key (bell): To call house phones or other guard units.

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
2.1881	24,5x28,8x26	VDS

Manuals

- 97001EI Central de Conserjeria ADS Ref 2536 V07_05.pdf
- 97001FAP Central de Conserjeria ADS Ref 2536 V07_05.pdf
- 97025 Resistencia conserjeria ADS V06_05.pdf

Declaration of conformity

- DOCF02536EN.pdf