



Product Code

F02829

ELECTRIC STRIKE MOD.500N

Reference

2829

EAN

8424299028293

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

-If the hinges are on the observer's right, it is a right DIN.

MOD.500

Electric mechanism model MOD.500, with reinforced steel latch able to withstand impacts up to 800kg. Dimensions:

-75(V)mmx21(H)mm

Recommended for wrought iron or steel gates with high transit flow. Includes cable output conduit for easy installation with a simple connector coupling

Technical Details

Consumption:
N, A 12Vac: 980mA
N-412 12Vdc: 400mA.

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.215	(height x width x depth) cm	Technologie
	3,4x16,3x2,7	GENERICA

Declaration of conformity

- DOCF02829ES.pdf