



Product Code

F02924

## LOCK RELEASE 300N-G

Reference

2924

EAN

8424299029245

## Description.

## Description

**Operating type.**

There are several types of door lock release mechanisms depending on the type of operation needed.

**N type Normal 12 Vac.** (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

**Universal**

This door lock release is made up of a UNIVERSAL electric mechanism which dimensions are:

104(V)x20(H)mm, if MAX version the size of the body changes to 91(V)mm. Flush mounted in wooden and metal frames.

Characteristic robust design and low power consumption.

**Reversible (Right DIN or Left DIN).**

Allows to open the door from right and left.

**Non-symmetrical.**

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

**DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

**Flush mounted Door lock.**

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

**G type flush shield.**

For doors with deadbolt entry.

G type metallic trim fitted with an electrical mechanism to form a flush-fit lock release with deadbolt entry.

**Dimensions: 25(H)x250(V)mm.**

## Technical Details

Consumption:

N, A 12Vac: 980mA

N-412 12Vdc: 200mA.

N-512 12Vdc: 150mA.

N-424 24Vdc: 120mA.

## Details.

Weight (kg)

0.311

Packaging measurements

(height x width x depth) cm

3,4x25x2,7

Video Door Entry system

Technologie

GENERICA

Declaration of conformity

- DOCF02924EN.pdf