



Product Code

F02927

LOCK RELEASE 300AD-G

Reference

2927

EAN

8424299029276

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

Type A Automatic 12Vac (Automatic operation and 12 Vac activation).

The lock release is unblocked when it receives a 12Vac voltage pulse. The lock release is blocked again once the voltage is cut off and the door opens and closes again mechanically. For proper installation, the automatic lock pin must be pressed in 3mm by the latch once the door is closed again.

Universal

This door lock release is made up of a UNIVERSAL electric mechanism which dimensions are: 104(V)x20(H)mm, if MAX version the size of the body changes to 91(V)mm. Flush mounted in wooden and metal frames. Characteristic robust design and low power consumption.

Reversible (Right DIN or Left DIN).

Allows to open the door from right and left.

Non-symmetrical.

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

G type flush shield.

For doors with deadbolt entry.

G type metallic trim fitted with an electrical mechanism to form a flush-fit lock release with deadbolt entry.

Dimensions: 25(H)x250(V)mm.

Technical Details

Consumption:

N, A 12Vac: 980mA

N-412 12Vdc: 200mA.

N-512 12Vdc: 150mA.

N-424 24Vdc: 120mA.

Details.

Weight (kg)

0.316

Packaging measurements

(height x width x depth) cm

3,4x25x2,7

Video Door Entry system

Technologie

GENERICA