



Product Code

F05224

KIT AC-MAX 4 DOORS

Reference

5224

EAN

8424299052243

Description.

Description

Access control kit for four doors. The kit consists of metal enclosure with power supply, networked access controller and IO expander. The controlled doors can be managed on both, input readers and output readers side, by RS485 (FPAC-MAX), in case of Wiegand readers only as input readers. Each controlled door has separate 0.2 A supply output for readers and 1.0 A supply output for lock and other door equipment. The back-up battery charging current can be set to 0.3 A or 0.6 A. The entire system is supplied from the power supply included in the kit.

COMPOSITION:

- Metal BOX-IP16.
- PWR4D 13.8Vdc
- AC-MAX-CU-4 central unit in TCP / IP network. It manages up to 4 doors each door with an input reader, therefore it allows the connection of up to 4 Wiegand readers or 8 FPAC-MAX fingerprint readers (4 input and 4 output).
- EXP4D I / O Expander- EXT4D I / O expansion module.

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system
305(V) x 325(H) x 100(P)	3.693	11x33x31,5	Technologie NO PE/VP

Access Control Technology

GENERICA

Manuals

- 970073EIPb DOC INST. KITS AC-MAX 5223 5224 V04_21.pdf
- 970073FAb DOC INST. KIT AC-MAX 2-4 PUERTAS V04_21.pdf
- 970074 DOC PWR2D-PWR4D ALIMENT. KIT AC-MAX 5223-5224 V12_20.pdf
- 970075 DOC BOX-IP-15_16 CAJA KIT AC-MAX 5223-5224 V01_21.pdf
- 970078b-1 GUIA INST. CABLEADO KITS AC-MAX 2-4 PUERTAS 5223 5224 V04_21.pdf
- 970078EIPb-2 GUIA INICIO AC-MAX LT v2.0 V04_21.pdf
- 970078FAb-2 START GUIDE AC-MAX LT v2.0 V04_21.pdf
- 970095_DOC_LICENCIA_USB_AC-MAX_KEY6-LKY_1608_v12_20.pdf
- 970212 ESQUEMA AC-MAX BOX 4D REF. 5224 v09_21.pdf

Declaration of conformity

- DOCF05224EN.pdf

Accessories



F02337

BATTERY 12V 7Ah



F05190

CITY KEYPAD READER



F05225

FPAC-MAX FINGERPRINT READER



F05293

KEYPAD W/PROXIMITY RESISTANT