

Product Code

F05225

## FPAC-MAX FINGERPRINT READER



Reference

EAN

5225

8424299052250

### Description.

---

#### Description

The FPAC-MAX is a biometric fingerprint reader equipped with a high quality optical sensor and ISO / IEC 14443A and MIFARE® proximity reader. Users can be recognized by comparing their fingerprint with those registered in the reader's memory (1: N mode) or with those registered on the MIFARE® card (1: 1 mode). The reader can store up to 1,900 fingerprints and is still able to recognize users relatively quickly. If 1: 1 mode is applied, the third (highest) recognition level is applied and maximum privacy is achieved.

The reader connects to the AC-MAX CU access controller via RS-485 (2-wire) power (2-wire) and Ethernet (UTP). Footprint registrations and deletions are managed by IP through the PC. The IP communication with the FPAC-MAX reader is encrypted under the AES128 CBC standards, which guarantee high resistance to unauthorized decryption. The configuration and management of the fingerprint database are carried out from the AC-MAX management software.

*NOTE: Before using the fingerprint reader it is necessary to check that the application of the device in certain conditions complies with the law.*

## Details.

Product measurements (height x width x depth) mm  
85x85x52

Weight (kg)  
0.3386

Packaging measurements (height x width x depth) cm  
7,7x23x10,5

Video Door Entry system  
Technologie  
NO PE/VP

Access Control Technology  
HUELLA

Manuals  
970077b DOC FPAC-MAX HUELLA PROX. MF AC-MAX 5225  
V04\_21.pdf

Declaration of conformity  
DOCF05225EN.pdf

## Accessories



F05223  
KIT AC-MAX 2 DOORS



F05223  
KIT AC-MAX 2 DOORS



F05223  
KIT AC-MAX 2 DOORS



F05223  
KIT AC-MAX 2 DOORS



F05223  
KIT AC-MAX 2 DOORS



F05223  
KIT AC-MAX 2 DOORS



F05224  
KIT AC-MAX 4 DOORS



F05224  
KIT AC-MAX 4 DOORS



F05224  
KIT AC-MAX 4 DOORS



F05224  
KIT AC-MAX 4 DOORS



F05224  
KIT AC-MAX 4 DOORS



F05224  
KIT AC-MAX 4 DOORS