



Product Code

F05559

## PUSHB. MARINE DUOX PLUS VID. AMP. SET

Reference

5559

EAN

8424299055596

### Description.

---

#### Description

Amplifier module to incorporate in steel, aluminum or mailboxes panels.

This design integrates audio and video functions in the same module. For video door entry systems.

The module includes the amplifier (audio/video unit) which incorporates the electronic circuits necessary for the operation of the audio/video system, door opening, etc... This has volume adjustments, both in the home-outdoor and home-outdoor direction, so that the installer can adjust the optimum level and the WIDE ANGLE COLOUR camera with integrated lighting and regulation system for the camera focus.

The camera image can be adjusted in different ways:

- By means of the voice-assisted configuration included in the amplifier module itself.
- By temporarily connecting a keyboard (ref. 7439).
- By means of the locally connected DUOX Programmer.

**System: DUOX PLUS (2-wire digital)**

#### Technical Details

##### Video:

- Sensor: 1/3 "CMOS color.
- Effective pixels> 340K. (the camera captures 720x480)

- Minimum external lighting: 0 lux. Since it has LEDs, no additional lighting is required.
- S / N> 45dB.
- Frame rate 25 fps.
- Resolution> 368x288 pixels.
- Video codec: H264 Highline Profile
- Auto iris.
- Auto BLC.
- Angle of vision 100° horizontal, 80° vertical.
- Fish eye correction.
- Color night vision through white LEDs.
- Pan & Tilt digital zoom.

Power: 18-24 Vdc

Consumption:

- idle: 240 mA.
- active audio: 560 mA.

Audio power house-street sense: 2W

Audio power street-dwelling sense: 0.15W

Adjustable volume in both directions

Operating temperature: -25 to 70 °C

## Details.

---

Weight (kg)

0.432447

Packaging measurements

(height x width x depth) cm

7,2x14,5x14

Video Door Entry system

Technologie

DUOX

## Manuals

- 970051c Placa MARINE  
Video Duox Plus  
V07\_21.pdf

Other images



Back view

