



Product Code

F05922

MDS CABLE TELEPHONE (100mtr)

Reference

5922

EAN

8424299059228

Description.

Description

MDS SYSTEM Buses in MDS Digital Systems (cabling): - AUDIO only: * Panel Bus: 4 wires and shielded twisted pair. * Central interconnection bus (FXL network): 4 wires and shielded twisted pair. * Decoders' Bus: 4 wires and shielded twisted pair. - AUDIO + VIDEO: * Panel Bus: 7 wires + shielded twisted pair + coax. * Central interconnection bus (FXL network): 4 wires and shielded twisted pair + coax. * Decoders' Bus + Video Distributor: 6 wires and shielded twisted pair + coax. Buses in MDS Direct Systems (cabling): - AUDIO only: * Panel Bus: 4 wires and shielded twisted pair. * General Input Bus to Interior Blocks or Bus between Interior Blocks: 4 wires and shielded twisted pair. * Decoders' Bus: 4 wires and shielded twisted pair. - AUDIO + VIDEO: * Panel Bus: 7 wires and shielded twisted pair + coax * General Input Bus to Interior Blocks or Bus between Interior Blocks: 4 wires and shielded twisted pair + coax. * Decoders' Bus + Video Distributor: 6 wires and shielded twisted pair + coax. Buses in MDS City Systems (cabling): - AUDIO only: * Panel Bus: 4 wires and shielded twisted pair. * General Input Bus (MDS Digital or MDS Direct) to Interior Blocks: 4 wires and shielded twisted pair. * Bus between Interior Blocks: 4 wires and shielded twisted pair. * Decoders' Bus: 4 wires and shielded twisted pair. - AUDIO + VIDEO: * Panel Bus: 7 wires and shielded twisted pair + coax * General Input Bus (MDS Digital or MDS Direct) to Interior Blocks: 4 wires and shielded twisted pair + coax. * Bus between Interior Blocks: 4 wires and shielded twisted pair + coax. * Decoders' Bus + Video Distributor: 6 wires and shielded twisted pair + coax. ADS SYSTEMS - AUDIO only: 3 wires - AUDIO + VIDEO: 3 wires + coax 4+N SYSTEMS - AUDIO Only: 4 common wires + n call wires - AUDIO + VIDEO: 7 common wires + n call wires + coax The installation of MDS systems is limited to BUS type cabling. A length of cable runs from the vertical line of the building connecting the exterior outdoor panel with the residences and also interconnecting the different blocks in the case of a residential complex. * Ref. 5922 BUS TELEPHONE CONNECTION: - cable comprised of 6 x 0.5 mm² wires- For interconnections on each floor between the decoder and the residential telephone. - They are fitted with 50 metre spools.

Technical Details

Fermax supplies a series of specially designed CABLES specially designed for MDS systems. The Fermax cables Ref. 5918 and Ref. 5919 are suitable for distances of up to 300 metres. We have various types of BUS in the system: * Ref. 5918 BUS AUDIO + DATA: - cable comprised of 4 x 1mm² wires + a shielded twisted pair (2 x 0.5 mm²). - For interconnections between panels-decoders - central systems. - They are fitted with 100 metre spools. * Ref. 5919 BUS VIDEO: - cable comprised of 3 x 1 mm² wires + a coaxial cable - For connections between the telecamera and the panel - video distributors. - They are fitted with 100 metre spools. * Ref. 59200 BUS CONNECTION MONITOR - cable comprised of 3 x 1mm² wires + 8 x 0.5mm² wires + coaxial. - For interconnection between the decoder + distributor and residential monitor on an individual floor level. - They are fitted with 100 metre spools. * Ref. 5922 BUS TELEPHONE CONNECTION: - cable comprised of 6 x 0.55 mm² wires - For interconnections on each floor between the decoder and the residential telephone. - They are fitted with 50 metre spools.

Details.

Weight (kg)

0.06

Packaging measurements

(height x width x depth) cm

9x27x27

Video Door Entry system

Technologie

GENERICA

Declaration of conformity

- DOCF05922EN.pdf