



Product Code

F06461

## ELECTRIC STRIKE 540ND-412 MAX

Reference

6461

EAN

8424299064611

### Description.

---

Description

#### Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

#### N-412 Normal type 12Vdc (Normal operation and 12 Vdc activation).

The lock release is unblocked for the time that the 12 Vdc voltage is applied.

#### Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

#### Symmetrical.

Allows to change hands, maintaining the body symmetry.

#### DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

#### Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

#### D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

#### Technical Details

##### Consumos:

- N, A 12Vac: 560mA
- N-412 12Vdc: 260mA.
- N-424 24Vdc: 180mA.
- N-512 12Vdc: 200mA.

N-524 12Vdc: 120mA.

##### Dimensiones:

Serie 540, 67(V)mmx20,5(H)mmx28(P)mm

**MAX Pestillo ajustable:** 3mm

Details.

Weight (kg)

0.1683

Packaging measurements

(height x width x depth) cm

2,7x10,2x3,2

Video Door Entry system

Technologie

GENERICA