



Product Code

F06575

7" VDS BASIC SMILE TOUCH MONITOR

Reference

6575

EAN

8424299065755

Description.

Description

FUNCTIONS - 7" capacitive touch screen to navigate through the door entry system menus. - Capacitive pushbuttons. - Hands-free audio communication (Press-to-talk mode also configurable). - Door opening. - Guard unit call. - Call volume control and Do-not-distrub (DND) option with programable time from 00:00 until 23:59. - Doormatic (Professional studio/office function) with configurable time (from 00:00 to 23:59). - Configurable ringtones (6 options). - Door bell. - Monitor address quickly and easily programmable from the monitor screen. - Audio volumen control. - Audio cancellation of the monitor microphone (MUTE). - Settings configuration throughout the screen menu (OSD). - Lift control. - Adjustment of brightness, contrast and color. - Auxiliary video input (CCTV camera connection). - Configurable direct pushbuttons (shortcuts), for additional configurable functions of the door entry system. **OPERATIONAL DESCRIPTION** **Capacitive pushbuttons** Activates/Deactivates the communication with the outdoor panel (it includes led). Door opening (it includes led). Wildcard: Auto-on / Main and secondary camera selection (it includes red led). **MENU:** for configuration and adjustments. Long touch (5 s.): access to the user's menu.Short touch: the screen shows the configured shortcuts. **7" capacitive touch screen** Screen touch: goes to the configuration and adjustments menu. User-friendly menu with grafic icons. **LED icons** Do not disturb mode **ACCESSORIES** Ref. 6565. Smile VDS white connector. Ref. 6562. Smile flush mounted decorative frame. Ref. 6551. Smile 7" flush box. Ref. 6566. Smile desktop support. **MECHANICAL FEATURES** **Appearance** Color: White. Material: ABS V0. Front Material: PMMA optical degree. **Dimensions** Surface: 185x172x20mm. 20mm protrusion from the wall once fixed. Flush-mounted: 209x196x4mm. 4mm protrusion from the wall once fixed. ref. 6551 7" Flush box: 186 x 198 x 46 mm **ELECTRICAL FEATURES** **Maximum estimated consumption:** - standby: 23 mA - video: 450 mA - audio + video: 720 mA - audio / video with activated magnetic loop: 1050 mA **Functioning temperature:** [-5, +40 °C] **Humidity:** [5%, 95%] **Resolution TFT 7":** - Hor.:

800 pixels - Ver.: 480 pixels **Video signal:** compound video signal 1Vpp, 75 ohm, 7 Mhz.

Technical Details

TECHNICAL SPECIFICATIONS Screen - Size 7". - Touch screen with capacitive technology. - Format 16:9 - Resolution 800x480 - Contrast rate 500/l. - Luminance (cd/m2) 400 nits. - Contrast, brightness and color control. **Audio features** - Loudspeakers: 1 x 1W. - Audio level adjustable during the operation. - Totally hands-free conversation. - Conversation privacy. - Selectable ringtones. **Power supply** - 18 Vdc. **Technology:** VDS - 5 wires / UTP Cat 5 / 3+Coax. **Connections VIDEO TERMINALS:** - V, M, V, M: video input and output from the outdoor panels. - Ct: camera activation. - Vaux, M: peripheral video input 75 ohm. Used for: Door bell camera activation. CCTV function. **CONNECTION TERMINALS: +, -:** power (18Vdc). **L:** data bus. **F1:** double additional function - Output activation of devices such as relays (FERMAX ref. 2013, 29001, etc.). - Input for an external panic button. It will be configured if the panic option is selected. **F2:** double function - Output activation of devices such as relays (FERMAX ref. 2013, 29001, etc.). - Output activation when pressing door opening. **T, -:** connections for the door bell pushbutton. **+A, -:** output connection for external FERMAX devices such as the call extension ref. 2040, light activator ref. 2438, etc.

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
0.5453	4,7x20,8x22	VDS

Manuals

- [97890Ab_Monitor_SMILE_TACTIL_Basic_VDS_V09_18.pdf](#)
- [97890Eb_Monitor_SMILE_TACTIL_Basic_VDS_V09_18.pdf](#)
- [97890Fb_Monitor_SMILE_TACTIL_Basic_VDS_V09_18.pdf](#)
- [97890Ib_Monitor_SMILE_TACTIL_Basic_VDS_V09_18.pdf](#)
- [97890Pb_Monitor_SMILE_TACTIL_Basic_VDS_V09_18.pdf](#)
- [97892b_Guia_rapida_Monitor_SMILE_TACTIL_Basic_VDS_V02_17.pdf](#)

Declaration of conformity

[DOCF06575EN.pdf](#)