



Product Code

F06750

UNIVERSAL ELECTRIC STRIKE 990N 10-24V MAX

Reference

6750

EAN

8424299067506

Description.

Description

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

Technical Details

- Consumption: N_MULTI-VOLTAGE 10-24V: 12Vac:250mA, 12Vdc:280mA, 24Vac: 500mA, 24Vdc:560mA
- Dimensions: 66(V) x 16(H) x 25.5(D)mm.
- MAX regulation: 2mm
- Holding force: 330Kg-f/3230N
- Temperature: -15°C to +40°C
- Cycles tested: 400,000

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
66(V)x16(H)x25.5(P)mm	0.1239	2,7x10,2x3,2	GENERICA

Accessories



F05207

CONTACTLESS PUSHBUTTON FLUSH MOUNTED



FE02892

L22-TYPE GREY SHIELD



FE02893

M-TYPE SHIELD



FE01076

MC740 G2 MAGNETIC CONTACT



F04802

P.S.U. DIN4 230VAC/12VAC-1A



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



FE02894

P22-TYPE GREY SHIELD



FE02973

S-TYPE SHIELD