



Product Code

F06958

CITYLINE WG MIFARE/EM PROXIMITY READER

Reference

6958

EAN

8424299069586

Description.

Description

Reader that lets you open the door by displaying a multi-frequency card or proximity keyring (EM (125KHz), MIFARE (13,56MHz) and HID (125KHz, ISOProxII). Only authorized cards or keyrings will trigger the device. No physical contact is necessary. Acoustic confirmation of the acceptance or rejection of the card or keyring presented. Recommended for interiors and exteriors.

The readers are Wiegand 26, allowing you to equip the access control installation with anti-sabotage security, as neither the door opening mechanism nor the exit button connection are built-in. These functions are supported by the door controller that uses the Wiegand protocol 26 and are therefore out of reach of tampering.

The door controller is installed indoors (secure zone) and the reader on the outside.

STAND-ALONE setup:

* Capacity up to 1,000 user cards or keyrings. * Requires door controller (ref. 5276) for connection and operation.

* Power supply 12Vcc.

STAND-ALONE Technical Features:

- No physical reader-card contact required. Reading distance 5 cm (card) or 1.5 cm (keyring).
- Acoustic information on actions.
- Very simple manual programming. By MASTER REGISTRATION and MASTER DEREGISTRATION cards.

- Stand-alone controller (Ref.5276) with 1 relay output.
- Electric lock activation by relay with programmable timing. Programmable 1 to 99 sec.

STAND-ALONE Programming

- Can be done in 2 ways:

By Master Cards.

IR programming keypad included with controller.

It is recommendable to install controller in the same flush box for just behind the wall installed, as this way programming with the IR keypad will be easier, as the programmer needs to have direct line of sight with the controller.

CENTRALIZED setup:

* Proximity card reader with capacity for up to:

1,020 user cards/keyrings with MDS Central Unit (ref. 2405). 2,048 user cards/key rings with AC+ Central Unit (ref. 4410).

* Requires door controller (ref. 4420) for connection and operation.

CENTRALIZED Technical Features

- No physical reader-card contact required. Reading distance 5 cm (card) or 1.5 cm (keyring).
- Acoustic information on actions.
- The reader can be used with other door controllers using Wiegand-26 (WG) protocols.
- Wiring: 5 wires to door controller.

CENTRALIZED Programming

Programming is done from the PC software corresponding to the central unit installed (ref. 2405 or ref. 4410). - For further information, see Door Controller Technical Features.

Technical Details

MECHANICAL CHARACTERISTICS

APPEARANCE

- 3mm aluminum.
- Continuous profile.
- Environmental protection (IP): 52 Shock protection (IK): 07
- DIMENSIONS
- Dimensions (HxV mm): 130 x 128
- Empty box ref. 8851 (HxVxD mm - included): 115 x 114 x 45

Upper box ref. 7061 (HxVxD mm - optional): 130 x 128 x 33

TECHNICAL CHARACTERISTICS

Feeding:

- Autonomous 12 Vdc
- Centralized: 12Vdc.
- Standby consumption: 12Vdc / 35mA
- Operating temperature: [-15°C, +55°C]
- Compatibility: EM(125KHz), MIFARE (13.56MHz) and HID (ISOProxII, 125KHz) cards/keychains
- Wiegand 26 proximity protocol.
- RF radiated power: 125KHz: 4.382dBuA/m, 13.56MHz: 2.02dBuA/m.

Details.

Weight (kg)	Packaging measurements	Video Door Entry system	Access Control Technology
0.560432	(height x width x depth) cm	Technologie	PROXIMIDAD
	7,3x14,8x13,8	NO PE/VP	

Manuals

- 970070 Lector Proximidad wiegand MIFARE NCity
V02_18.pdf