



Product Code

F07286

MDS DIRECT CITY AUDIO PANEL COLOUR

Reference

7286

EAN

8424299072869

Description.

Description

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.

New Cityline Panel:

CityLine is the "continuous profile" outdoor panel line for buildings.

This new panel model is more robust, more luxurious and higher design and functional quality. The new design, in its video entry version, includes audio and video functions in the same module.

Colour aluminium

Dialling keypad.

CTC Door status signalling switch contact.

This mechanism allows several applications thanks to its high-reliability C/No/Nc gold contact microswitch. Maximum contact intensity is 2A-230Vac. Shows whether the door is open or closed. Indispensable in security and alarm installations in banks, laboratories, jewellery stores and all premises that call for door opening with automatic blocking of another and vice versa. See

installation example on page 61 of the DOOR LOCK RELEASE CATALOGUE. This model does not admit version MAX

MDS Direct system: Simplified BUS installation digital audio and video door entry system that lets you manage large buildings and average sized residential complexes.

Recommended for.

- Individual buildings:

Up to 99 homes and 5 accesses (between audio and video panels) and 1 central guard unit.

Up to 99 homes and 9 accesses (between audio and video panels) if there is no central guard unit.

- In residential complexes:

- MDS Direct interior block combined with MDS Digital or Direct general entrances: Up to 99 interior blocks of 99 homes with a maximum of 9 accesses per block.

- MDS Direct MDS City or ADS interior block combined with MDS Direct general entrances: Up to 5 general entrances and 1 central guard unit or 9 general entrances without guard unit.

No Central Guard Unit required. Includes access control by keypad.

MDS systems require floor Decoders to connect the homes to the installation BUS and act as insulators. Home-panel communication is private.

Wiring:

- Audio: 6-wire bus.

- Video: audio bus + Coaxial (video) + 2 power supply wires.

Maximum distance in the installation depending on the cable section used (see technical manuals).

Technical Details

Two-way volume control

Operating temperature: -10 to 60 °C

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
1.061821	6,9x20x36,2	MDS

Manuals

- 97685Ab PLACA CYTY MDS DIRECT REF 7286-7287
V11_13.pdf
- 97685Eb PLACA CYTY MDS DIRECT REF 7286-7287

V11_13.pdf

- 97685Fb PLACA CYTY MDS DIRECT REF 7286-7287
V11_13.pdf
- 97685Ib PLACA CYTY MDS DIRECT REF 7286-7287
V11_13.pdf

Declaration of conformity

- DOCF07286ES.pdf