



Product Code

F07315

COLOUR VDS DIGITAL CITY PANEL W/PROX.

Reference

7315

EAN

8424299073156

Description.

Description

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc. Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system to adjust the camera lens.

Reader that enables door opening when a proximity card, similar to a credit card, approaches. Only authorized cards will activate the device. No physical contact is necessary.

New Cityline Panel:

CityLine is the "continuous profile" outdoor panel line for buildings.

This new panel model is more robust, more luxurious and higher design and functional quality. The new design, in its video entry version, includes audio and video functions in the same module.

Colour aluminium

Dialling keypad.

Backlit LCD 2 line display, 16 characters each.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

Technical Details

Two-way volume control

Operating temperature: -10 to 60 °C

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie	Access Control Technology
1.6874514	6,9x20x45,5	VDS	PROXIMIDAD

Manuals

970112_Normativa_Modulo_radiofrecuencia_V10_17.pdf

97486Pg_Man_Prog_Placas_Direct-Dig_VDS-BUS2-DUOX_V09_14.pdf

97516b_M_Inst_Placas_NCity-NMarine_Direct-Digital_VDS_V07_14.pdf

97598c_Lector_Proximidad_Centralizado_NCity_V09_16.pdf

Declaration of conformity

DOCF07315EN.pdf