



Product Code

F07470

DUOX PLUS SKYLINE DISPLAY

Reference

7470

EAN

8424299074702

Description.

Description

The **Duox Plus display module** allows the search and display of the list of neighbours (electronic directory) by means of the navigation buttons (arrow keys), as well as informing about the communication status.

The call to apartments can be made in two ways:

- by entering the corresponding code assigned to the property + the "bell" key.
- by searching in the electronic directory the user's name (navigation buttons) and once found by pressing the "bell" key.

The navigation buttons also allow you to move through the programming menu.

SKYLINE panel

The SKYLINE electronic and video door entry panel is a robust and elegant panel, which stands out for its durability and beauty, resistance and reliability.

SKYLINE is Fermax's line of continuous profile, modular composition audio and video door entry panels. The line is made up of 8 frames of different sizes where the different modules can be easily fitted together: pushbuttons, card slot, camera, amplifier, access control, etc. The frames allow a certain number of modules to be coupled together. There are two sizes of modules: V and W. W modules are twice the size of V modules.

Modules sizes.

- V module: 105.2x47.5 mm (width-height).
- W module: 105.2x95 mm (width-height).

It is possible to combine two or more panels, as long as they are of the same series, to have a greater capacity of buttons and accessories.

System: DUOX PLUS (2-wire digital)

Technical Details

IPK-437

Technical specifications of the display:

- Size: 3.5 inches
- Format: 4:3
- Resolution: 320 x 240 pixels
- Colours: 262.000
- Contrast rate: 500/1
- Viewing direction: 12 o'clock
- Luminance (cd/m2): 400 nits
- Viewing angle: 160H / 160V
- Back lighting: 6 LED diodes
- Directory capacity: 10,000 users.
- Supply voltage (through the CN1):
5V input (pin 1) with a 5% tolerance.
- PWR input: 12Vdc + 5% (DUOX)
- Total consumption: 88mA +10% (STANDBY); 134mA +10% (TFT ON)
- Operating temperature: -25°C, 70°C
- Relative humidity: 5% - 95 %

Module dimensions.

- Module W: 105.2x95 mm (width-height).
- Includes Wiegand-26/DataClock input port via CN2 Reader connector. Compatible with 7440 reader

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.3262	(height x width x depth) cm	Technologie
	13,5x10x6	DUOX

Manuals

- 970005F Manual Mode LECTURE-ECRITURE V08_17.pdf
- 97830E Manual software DISPLAY PLUS V04_22.pdf
- 97830F Manual software DISPLAY PLUS V04_22.pdf
- 97830I Manual software DISPLAY PLUS V04_22.pdf
- 97869Ah_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Eh_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Fh_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Ih_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Ph_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf