



Product Code

F09455

DUOX PLUS VEO DDA 4.3" MONITOR

Reference

9455

EAN

8424299094557

Description.

Description

El monitor VEO está fabricado en plástico ABS de alto impacto. Acabado texturizado para facilitar la limpieza y protección ultravioleta para que sea más resistente a la luz solar. VEO incluye una pantalla panorámica a color de 4,3" (16:9). El diseño único y exclusivo del auricular incorpora un imán que facilita al usuario el posicionamiento del mismo asegurando un colgado correcto al finalizar la conversación. Su diseño balanceado de líneas puras es distintivo, moderno y minimalista. VEO se integra en el ambiente. Cuando se recibe una llamada, la imagen aparece automáticamente. Cuando se descuelga el auricular, comienza la conversación con el visitante. La imagen desaparece automáticamente tras 90 segundos o cuando se cuelga el auricular. Para abrir la puerta pulsar el botón.

ACCESORIOS:

- 9447 CONECTOR MONITOR VEO/VEO-XS DUOX Para montaje del monitor sobre la superficie de la pared.
- 9410 SOPORTE DE SOBREMESA MONITOR VEO Los soportes de sobremesa Fermat permiten contestar a una llamada de la placa de calle, desde el escritorio del despacho, sin necesidad de interrumpir su trabajo. Fabricado en acero inoxidable de la máxima

calidad (AISI 316L). Requiere también del conector correspondiente.

- 3389 MARCO UNIVERSAL LARGE 210X240 De formato extra plano, fabricado en plástico ABS de alto impacto, tiene un acabado tipo texturizado fino. En reposición, permite cubrir el hueco dejado por equipos anteriores. Dimensiones 210 x 240 x 10 mm.

Technical Details

GENERAL CHARACTERISTICS

Technology: DUOX PLUS (non-polarised 2 wire full digital system)

Audio/Video system: Audio/Video Color

Set-up (Installation): Surface mounted (order connector ref. 9447 separately)

Desktop support: Yes (ref. 9410)

Handset with magnet to facilitate the hang up: Yes

Induction loop : Yes

Screen dimensions: 4,3" (Panoramic 16:9)

Screen resolution (H x V): 480 x 272

Color of the product: Matt white

Number of pushbuttons: 4

Kind of pushbuttons: Mechanical (silicone)

Number of leds for lighted indications: 1 (red with 3 states: always ON, slow/fast blinking)

PROGRAMMING OF THE TERMINAL ADDRESS

From the terminal: From the OSD menu

From the outdoor panel or guard unit: Yes

From the outdoor panel throughout the apartment door bell: Yes

FEATURES

Automatic picture capture when the visitor calls (PHOTOCALLER): Yes (1 photo/call, until 150 photos, 368 x 288 pixels). This feature can be enabled by the user. Disabled by default.

Guard unit call: Yes (by means of the door release button)

Auto-on: Yes (with 3 outdoor panels/cameras)

OSD menu: Yes

Additional function F1: Yes (Button F1 sends a negative and/or command)

Additional function F2: Yes (it only sends command, no negative)

Apartment door bell differentiated from the outdoor panel: Yes

Connection for additional devices (call extension, light/buzzer activator, etc.): Yes (ref. 2040, ref. 2438, ref. 3267)

Additional terminals on the same address: Yes, max. 2 additional terminals (additional power supply can be required)

Doormatic (automatic door release for offices, etc.): No

ADJUSTMENTS

Date and time: Yes

Ring tones selection: Yes (5). Configurable for Block Panel 0, Block Panel 1, General Entrance Panel 0 and Concierge unit.
 Call volume control: Yes (10 levels by OSD menu)
 Do-not-disturb mode: Yes (by OSD menu) + Red led indication
 Audio volume control: Yes (10 levels by OSD menu)
 Brightness, color and contrast control: Yes (by OSD menu)

TECHNICAL FEATURES

Product dimensions (width x height x depth) mm: 200 x 200 x 23 (44 including handset)
 Time to answer or open the door since the call is done: 30 s.
 Conversation time: 90 s.
 Conversation privacy: Yes
 Voltage: 18-24 Vdc
 Maximum consumption: 5.2 W
 Standby consumption: 0.8 W
 Working temperature (°C, °F); Humidity: [-5°C, +40°C][23°F, 104°F]; [0%, 90%]
 Line adaptor included in the terminal: Yes (A, C, default position OFF)
 Connections: Bin, Bin, Bout, Bout, -, A+, F1, T

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
200 x 200 x 44	0.5449	5,1x22,2x20,7	DUOX

Manuals

- 970143Ac_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Ec_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Fc_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Ic_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Pc_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970159c_Monitor_VEO_duox_NEW_V05_23.pdf
- 970160b_Guia_rap_monitor_VEO_duox_NEW_V05_23.pdf

Declaration of conformity

- DOCF09455ES.pdf

Accessories



F09447

DUOX PLUS CONNECTOR



F03389

UNIVERSAL FRAME LARGE



F09410

VEO MONITOR DESKTOP SUPPORT

Video formativo

- <https://youtube.com/playlist?list=PLf1YNFmssC37H-1CN64lo6ND28rmVsQit>