



Product Code

F30701

## LOCK RELEASE 540N-412-S MAX

Reference

30701

EAN

8424299307015

### Description.

---

Description

#### **Flush mounted Door lock.**

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanism and a shield if it is flush mounted.

#### **Reversible (Right DIN or Left DIN).**

Lets you open the door from right and left.

#### **Symmetrical.**

Allows to change hands, maintaining the body symmetry.

#### **DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

### Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

### N-412 Normal type 12Vdc (Normal operation and 12 Vdc activation).

The lock release is unblocked for the time that the 12 Vdc voltage is applied.

### Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

### S type flush shield.

For access doors.

S type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release.

**Dimensions: 25(H)x160(V) mm.**

### Details.

---

Weight (kg)	Packaging measurements	Video Door Entry system
0.2449	(height x width x depth) cm	Technologie
	3,4x16,3x2,7	GENERICA

### Declaration of conformity

- DOCF30701EN.pdf