



Product Code

F40702

CITY PANEL DUOX PLUS S1 AP101

Reference

40702

EAN

8424299407029

Description.

Description

Installed at the accesses to the building, it allows communication with the homes, opening the door, calling the concierge, etc.

CityLine Outdoor Panel.

Cityline is the "continuous profile" outdoor panel line for buildings.

This model of panel is more robust and of greater aesthetic and functional quality. It integrates audio and video functions in the same module in its video door entry version.

It is characterised by its curved-convex profile, maintaining the same characteristics as its predecessor, the City Classic. There is total compatibility between both models, ensuring their immediate replacement and replacement.

It is made of anodized aluminum, highly resistant to weather and climate changes (IP43 IK07). It incorporates new materials such as chrome zamak in heads and buttons

The front of the amplifier is made of aluminium and the interior is protected by a stainless steel grill.

The Cityline panel does not include the flush or surface box. This must be ordered separately.

It is possible to combine two or more panels, as long as they are of the same series. In order to fit them perfectly, a set of separators must be used for every two outdoor panels installed between their flush boxes.

Aluminium colour.

Injected zamak **call buttons** with chrome finish, in line with the curved profile of the panel. Waterproof for exteriors. Equipped with special gold-plated contacts for greater durability.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

Pushbuttons include a polycarbonate card holder (front access), to house a label with the homeowner's name and door number. Integrated lighting allows the cardholders to be viewed, even in complete darkness.

System: DUOX PLUS (2-wire digital)

Technical Details

Lighting LED consumption: 3.5 mA per card slot.

Series 1 Outdoor Panel.

- Panel dimensions: 130x128 mm (width-height).
- Flush box measurements: 115x114x45 mm (width-high-deep).
- Surface box measurements: 130x128x33 mm (width-high-deep).

Power supply: 18-24 Vdc

Consumption:

- Standby: 94 mA.
- Active audio: 550 mA.

IPK-437

Audio power home-street direction: 2W

Audio power street-home: 0.15W

Volume can be adjusted in both directions

Operating temperature: -25 to 70 °C

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.629868	(height x width x depth) cm	Technologie
	7,3x14,8x13,8	DUOX

Declaration of conformity

- DOCF40704EN.pdf