

Productcode

F44348

# MARINE PANEL DUOX PLUS ST1 CP201



Referentie

44348

EAN

8424299443485

## Omschrijving.

---

### Omschrijving

Installed in the accesses to the building, they allow communication with the dwellings, opening the door, calling the concierge, etc.

It incorporates a WIDE ANGLE COLOUR camera with integrated lighting and a regulation system for the focus of the camera. The camera image can be adjusted in different ways:

- By means of the voice-assisted configuration included in the amplifier module itself.
- By temporarily connecting a keyboard (ref. 7439).
- By means of the locally connected DUOX Programmer.

### Marine Outdoor Panel.

MARINE is the Fermax IP54 IK09 vandal-proof outdoor panel. It is made of 2.5mm thick stainless steel. AISI 316L steel type.

Marine is the perfect choice for installation in those places with extreme weather conditions or in hazardous environments, humid or corrosive climates.

The Marine outdoor panels do not include the flush or surface box. This must be ordered separately. The surface boxes include a protective hood.

It is possible to combine two or more panels, provided they are of the same series. In order to fit them perfectly, a joining bolts set must be used for every two plates installed between their flush boxes.

Steel colour.

The vandal-resistant **call buttons**, made of stainless steel and with an anti-locking system, resist any impact.

The buttons include a card holder to house a label with the homeowner's name and door number.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

#### **System: DUOX PLUS (2-wire digital)**

Aanvullende technische details

Lighting LED consumption: 3.5 mA per card slot.

#### **Video:**

- Sensor: 1/3" color CMOS.
- Effective pixels > 340K. (the camera captures 720x480)
- Minimum external illumination: 0 lux. As it has LEDs, no additional lighting is required.
- S/N >45dB.
- Frame rate 25 fps.
- Resolution > 368x288 pixels.
- Video codec: H264 Highline Profile
- Auto iris.
- Auto BLC.
- Viewing angle 100° horizontal, 80° vertical.
- Fisheye correction.
- Color night vision through white LEDs.
- Pan & Tilt digital zoom.

#### **ST1 Series Outdoor Panel.**

- Panel dimensions: 150x180 mm (width-height).
- Measures flush box: 130x160x55 mm (width-high-deep).
- Surface box measurements: 154x184x95 mm (width-high-deep).

- Hood measurements: 154x184x40 mm (width-high-deep).

Power supply: 18-24 Vcc

Consumption:

- Standby: 240 mA.
- Active audio: 560 mA.

IP65 IK09

Audio power home-street direction: 2W

Audio power street-home: 0.15W

Volume can be adjusted in both directions

Operating temperature: -25 to 70 °C

Details.

---

Gewicht product verpakt (kg)	Afmetingen verpakking (cm)	VP-technologie
1.044501	21x15,8x7,8	DUOX

Handleidingen

- 970051c Placa MARINE Video Duox Plus V07\_21.pdf
- 97737\_Limpieza\_Placas\_Marine\_V04\_20.pdf