



Product Code

F48505

1/W COLOUR VDS VIDEO CITY KIT PANEL

Reference

48505

EAN

8424299485058

Description.

Description

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc. Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system to adjust the camera lens.

Colour aluminium

Injected zamak chrome finish Call buttons, in line with the curved panel profile. Sealed for outdoors. Equipped with special gold plated contacts for lasting durability.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

Pushbuttons include a polycarbonate card slot (front access) to insert a label with the home owner's name and door number. Built in lighting lets you see the card slots, even in pitch dark.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video). Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit. Maximum distance from first access to last

home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

- Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).
- Maximum distance from first access to last home: 200 m.

Technical Details

- Two-way volume control
- Operating temperature: [-25°C, +70°C]

Details.

Product height (mm)	Product width (mm)	Weight (kg)	Packaging measurements (height x width x depth) cm
128	130	0.6998734	7,3x14,8x13,8

Video Door Entry system

Technologie

VDS

Manuals

- 97584 Sintesis Voz Poliglota V06_10.pdf
- 97707 Programacion abrepuertas Kits VDS V01_13.pdf
- 97716 Placa Kit Video 1-2L VDS V04_13.pdf

Declaration of conformity

- DOCF48505EN.pdf