



Product Code

F54337

MARINE VIDEO PANEL VDS ST1 CP 101

Reference

54337

EAN

8424299543376

Description.

Description

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc. Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system to adjust the camera lens.

Fermax Marine Line in stainless steel.

Marine is the anti-vandal panel line manufactured in 2.5 mm thick stainless steel.. Straight lines that highlight the quality of the steel. State of the art technology and resistance to even the most corrosive, humid and dangerous atmospheres.

The anti-vandal pushbuttons, made in stainless steel and with anti-blocking system, withstand any impact.

Buttons include a card slot to insert a label with the name of the home owner and door number.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

Technical Details

Two-way volume control

Operating temperature: -25 to 70 °C

IP65 IK09

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
1.5998124	21x15,8x7,8	VDS

Manuals

- 97537_Mapeado_Placas_Nueva_Cityline_VDS-BUS2_V07_12.pdf
- 97639_Placas_VDS_NMarine_V07_14.pdf
- 97737_Limpieza_Placas_Marine_V04_20.pdf

Declaration of conformity

- DOCF54337EN.pdf