



Product Code

F67521

UNIVERSAL LOCK RELEASE 990A-P22 12-24V MAX

Reference

67521

EAN

8424299675213

Description.

Description

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

P22 type flush shield.

For access doors.

P22 type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release. Recommended for smaller-sized aluminium and PVC frames.

Dimensions: 22(H)x130(V) mm.

Technical Details

- Consumption: A_MULTI-VOLTAGE 10-24V: 12Vac:250mA, 12Vdc:250mA, 24Vac: 500mA, 24Vdc:560mA
- Dimensions: 66(V) x 16(H) x 25.5(D)mm.
- MAX regulation: 2mm
- Holding force: 330Kg-f/3230N
- Temperature: -15°C to +40°C
- Cycles tested: 400,000

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.1727	(height x width x depth) cm	Technologie
	3,4x16,3x2,7	GENERICA

Declaration of conformity

- DOCF67521EN.pdf