

Product Code

F70031

CITY PANEL 4+N S4 AP203

Reference

70031

EAN

8424299700311

Description.

Description

Installed at the entrances to the building, they allow communication with the homes, opening the door, calling the concierge, etc.

New CityLine plate.

Cityline is the line of "continuous profile" street panels for buildings.

This new model of plate is more robust, more luxurious and of higher aesthetic and functional quality. The new design integrates, in its video intercom version, the audio and video functions in the same module.

It is characterized by its curved-convex profile, maintaining the same characteristics of its predecessor. There is total compatibility between both models, ensuring immediate replacement and replacement.

They are made of anodized aluminum, highly resistant to weather and climate changes. Incorporates new materials such as chrome-plated zamak on heads and buttons

Cityline plates do not include the recessed or surface box. This must be requested separately.

It is possible to combine two or more plates, as long as they are from the same series. To fit them perfectly, a set of spacers must be used for every two plates that are installed between their mounting boxes.

Aluminum color.

Injected zamak call buttons with chrome finish, in line with the curved profile of the plate. Waterproof for outdoors.

Equipped with special gold-plated contacts that provide greater durability.

Pressing the call button is confirmed by an acoustic warning light emitted by the amplifier.

The pushbuttons include a polycarbonate card holder (front access), to house a label with the name of the homeowner and the door number. Integrated lighting that allows you to view the card holders, even in complete darkness.

Conventional System: uses common wires for the entire installation plus 1 call (or call return) wire per home.

Recommended in small/medium-sized buildings (up to approximately 50 neighbors), with several entrances and a concierge center. For urbanizations with general entrance and inner blocks.

Cabling:

- Intercom: 4 common wires + N (1 call wire per home).
- Video intercom: 7 common wires + 1 video coaxial + N (1 call wire per home).

Maximum installation distance depending on the section of the cable used (consult technical manuals)

Technical Details

- Adjustable volume in both directions
- Operating temperature: -10 to 60 °C

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.821018	(height x width x depth) cm	Technologie
	6,9x20x26,7	4+N

Manuals

- 97448d DOC Amplificador 4n NCity Perf Cont V11_10.pdf