



Product Code

F73852

## DUOX PLUS DIGITAL CITY AUDIO PANEL

Reference

73852

EAN

8424299738529

### Description.

---

#### Description

Installed in the accesses to the building, it allows communication with the dwellings, door opening, call to the guard, etc..

#### CityLine panel.

Cityline is the "monoblock profile" outdoor panel line for buildings.

This panel model is more robust and of greater aesthetic and functional quality. It integrates, in its video door entry version, the audio and video functions in the same module.

It is characterized by its curved-convex profile maintaining the same characteristics of its predecessor the City Classic. There is total compatibility between both models, ensuring their immediate replacement and replacement.

It is made of anodized aluminium, highly resistant to weather and climate changes (IP43 IK07). It incorporates new materials such as chrome-plated zamak in the covers and the pushbuttons. The front of the amplifier is made of aluminium and the interior is protected by a stainless steel grid.

The Duox Plus display module allows the search and display of the list of neighbours (electronic directory) by means of the navigation buttons (arrow keys), as well as informing about the communication status.

The call to apartments can be made in two ways:

- by entering the corresponding code assigned to the property + the "bell" key.
- by searching in the electronic directory the user's name (navigation buttons) and once found by pressing the "bell" key.

The navigation buttons also allow you to move through the programming menu.

The Cityline panel does not include the flush or surface box. This must be ordered separately.

It is possible to combine two or more panels, as long as they are of the same series. To ensure that they are perfectly matched, one set of joining bolts be used for every two panels installed between their flush-mounted boxes.

Aluminium colour.

Backlit keypad.

### **System: DUOX PLUS (2-wire digital)**

#### Technical Details

The DIGITAL panels have a backlit keypad and a 3.5" electronic directory for calling the apartments.

The call to the apartment is made by entering the corresponding code assigned to the apartment + the "bell" key.

Electronic directory: allows the search of the names (owners of the properties...) through the display and the navigation buttons.

Access Control: through the numeric keypad it incorporates access control functions by means of keypad codes (previously programmed). The keypad allows up to 10,000 codes to open the door.

#### Technical Specifications Display:

- Size: 3.5 inches
- Format: 4:3
- Resolution: 320 x 240 pixels
- Colours: 262,000
- Contrast ratio: 500/1

- Display direction: 12 o'clock
- Luminance (cd/m2): 400 nits
- Viewing angle: 160H / 160V
- Backlighting: 6 LEDs
- Directory capacity: 10,000 users.
- Supply voltage (through CN1):  
5 V input (pin 1) with a 5% tolerance  
PWR input: 12 Vdc + 5% (DUOX)
- Total consumption: 88 mA +10% (STANDBY); 134 mA +10% (TFT ON)
- Operating temperature: -25°C, 70°C
- Relative humidity: 5% - 95 %.

Display Module size:

- W module: 105.2x95 mm (width-height).

Duox backlit display, 3.5" TFT high brightness for outdoors that facilitates and enhances the possibilities of the board.

- Integrated ONE-TO-ONE functions: visual icons to show the communication state: calling, conversation, door open
- Can integrate personalised images.
- Can integrate customised messages.
- Directory keys and possibility of using the keyboard as alphanumeric.
- Date and time indication.
- Combination with pushbutton panels (max. 8 pushbuttons).
- Possibility of connecting readers with Wiegand-26 and Data Clock protocol
- Management from PC and connection through RS-485.

PANEL SERIE 7

- Panel dimensions: 130x341 mm (width-height).
- Flush box dimensions: 115x328x45 mm (width-high-depth).
- Surface box dimensions: 130x341x33 mm (width-high-depth).

Power supply: 18-24 Vdc

Consumption:

- stand-by: 260 mA.
- Active audio: 580 mA.

IP43 – IK07

Audio capacity home-outdoor panel: 2W

Audio capacity outdoor panel-home: 0.15W

Two-way volume control

Operating temperature: -25 to 70 °C

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
1.252446	(height x width x depth) cm	Technologie
	6,9x20x36,2	DUOX

Manuals

- 97830E Manual software DISPLAY PLUS V04\_22.pdf
- 97830F Manual software DISPLAY PLUS V04\_22.pdf
- 97830I Manual software DISPLAY PLUS V04\_22.pdf
- 97869Ag\_DISPLAY\_SKYLINE\_DUOX\_PLUS\_V05\_23.pdf
- 97869Eg\_DISPLAY\_SKYLINE\_DUOX\_PLUS\_V05\_23.pdf
- 97869Fg\_DISPLAY\_SKYLINE\_DUOX\_PLUS\_V05\_23.pdf
- 97869Ig\_DISPLAY\_SKYLINE\_DUOX\_PLUS\_V05\_23.pdf
- 97869Pg\_DISPLAY\_SKYLINE\_DUOX\_PLUS\_V05\_23.pdf

Declaration of conformity

- DOCF73851EN.pdf