



Productcode

F73891

CITY PANEL DUOX PLUS S4  
CVP101 DDA

Referentie

73891

EAN

8424299738918

## Omschrijving.

### Omschrijving

Installed in the accesses to the building, they allow communication with the dwellings, opening the door, calling the concierge, etc.

### CityLine Outdoor Panel.

Cityline is the "continuous profile" outdoor panel line for buildings.

This model of panel is more robust and of greater aesthetic and functional quality. The design integrates, in its video door entry version, the audio and video functions in the same module.

It is characterised by its curved-convex profile, maintaining the same characteristics as its predecessor, the City Classic. There is total compatibility between both models, ensuring their immediate replacement.

It is made of anodized aluminum, highly resistant to weather and climate changes (IP43 IK07). It incorporates new materials such as chrome zamak in heads and buttons.

The front of the amplifier is made of aluminium and the interior is protected by a stainless steel grille.

It incorporates a WIDE ANGLE COLOUR camera with integrated lighting and a regulation system for the camera's focus. The camera image can be adjusted in different ways:

- By means of the voice-assisted configuration that includes the amplifier module itself.
- By temporarily connecting a keyboard (ref. 7439).
- By means of the locally connected DUOX Programmer.

The Cityline panels do not include the flush or surface box. This must be requested separately.

It is possible to combine two or more panels, provided they are of the same series. In order to fit them perfectly, a set of separators must be used for every two panels installed between their flush boxes.

Aluminium colour.

Injected zamak **call buttons** with chrome finish, in line with the curved profile of the panel. Waterproof for exteriors. Equipped with special gold-plated contacts for greater durability.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

Pushbuttons include a polycarbonate card holder (front access), to house a label with the homeowner's name and door number. Integrated lighting allows the cardholders to be viewed, even in complete darkness.

The outdoor panel includes the **OneToOne information module with inductive loop**. The "OneToOne" module with inductive loop shows the status of the panel by means of 4 LED icons.

These icons symbolize:

- Call.
- Conversation.
- Door opening.
- Channel busy.

In addition, each of the sounds and audio played by the amplifier, are emitted by the inductive loop to the devices of the disabled people.

**System:** DUOX PLUS (2-wire digital)

## Aanvullende technische details

Lighting LED consumption: 3.5 mA per card slot.

**Video:**

- Sensor: 1/3" color CMOS.
- Effective pixels > 340K. (the camera captures 720x480)
- Minimum external illumination: 0 lux. As it has LEDs, no additional lighting is required.
- S/N >45dB.
- Frame rate 25 fps.
- Resolution > 368x288 pixels.
- Video codec: H264 Highline Profile
- Auto iris.
- Auto BLC.
- Viewing angle 100° horizontal, 80° vertical.
- Fisheye correction.
- Color night vision through white LEDs.
- Pan & Tilt digital zoom.

**Series 4 Outdoor Panel.**

- Panel dimensions: 130x199 mm (width-height).
- Measures flush box: 115x185x45 mm (width-high-deep).
- Surface box measurements: 130x199x33 mm (width-high-deep).

Power supply: 18-24 Vdc

## Consumption:

- at rest: 240 mA.
- Active audio: 560 mA.

IPK-437

Audio power home-street direction: 2W

Audio power street-home: 0.15W

Volume can be adjusted in both directions

Operating temperature: -25 to 70 °C

Details.

Gewicht product verpakt (kg)	Afmetingen verpakking (cm)	VP-technologie
0.74035	6,9x20x26,7	DUOX

Handleidingen

- 970050c Placa CITY Amplif DUOX PLUS V07\_21.pdf
- 970111b Modulo OneToOne BUCLE V03\_20.pdf