



Product Code

FE02923

LOCK RELEASE N-2001 CHROME

Reference

2923

EAN

8424299029238

Description.

Description

Surface door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanism and a shield if it is flush mounted.

Reversible (Right DIN or Left DIN).

Allows to open the door from right and left.

Non-symmetrical.

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Type 2001 surface cover.

One-piece cover 146mm. CHROME finish.

Visible attachment on frame

Technical Details

Consumption:

N, A 12Vac: 980mA

Details.

Weight (kg)

0.38

Packaging measurements

(height x width x depth) cm

2,5x14,9x3,8

Video Door Entry system

Technologie

GENERICA