

Product Code

FE02956

LOCK RELEASE MOD.460N BISEL



Reference

2956

EAN

8424299029566

Description.

Description

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

Serie 460

This door lock is made up of an Electric mechanism model MOD.460, AMÉRICA, which dimensions are:

75(V)mm

The deeper latch and shield make it particularly suitable for metal frames. Also suitable for American or British locks.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Technical Details

Consumption:

N 12Vac: 980mA

N-412 12Vdc: 400mA.

N-512 12Vdc: 200mA.

Details.

Weight (kg)

0.2865

Packaging measurements

(height x width x depth) cm

4,3x16x3,2

Video Door Entry system

Technologie

GENERICA