



Product Code

FE02968

LOCK RELEASE 300N-524-S

Reference EAN

2968 8424299029689

Description.

Description

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

Universal

This door lock release is made up of a UNIVERSAL electric mechanism which dimensions are:

 $104 (V) x 20 (H) mm, if MAX \ version \ the \ size \ of \ the \ body \ changes \ to \ 91 (V) mm. \ Flush \ mounted \ in \ wooden \ and \ metal \ frames.$

Characteristic robust design and low power consumption.

Reversible (Right DIN or Left DIN).

Allows to open the door from right and left.

Non-symmetrical.

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

DIN STANDARD



establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- -If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N-524 Inverted type 24Vdc (Inverted Operation and 24 Vdc activation)

The door release is automatically unlocked when the 24 Vdc pulse stops.

S type flush shield.

For access doors.

S type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release.

Dimensions: 25(H)x160(V) mm.

Technical Details

Consumption:

N, A 12Vac: 980mA N-412 12Vdc: 200mA. N-512 12Vdc: 150mA. N-424 24Vdc: 120mA.

Details.

Weight (kg)

Packaging measurements

Video Door Entry system

0.2925

(height x width x depth) cm

Technologie

3,4x16,3x2,7

GENERICA