



Product Code

FE03004

LOCK RELEASE MOD.6000N

Reference EAN

3004 8424299030043

Description.

Description

Surface door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

Serie 6000

Surface with deadbolt recess. Surface door lock with attachment concealed on frame, reversible, for doors with locks with latch/bolt. Does not allow inverted operation or MAX version.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.



Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- -If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Technical Details

Consumption:

N, A 12Vac: 980mA N-412 12Vdc: 200mA. N-512 12Vdc: 150mA.

Details.

Video Door Entry system Weight (kg) Packaging measurements

0.5955 (height x width x depth) cm Technologie **GENERICA**

5,5x13,5x6,5

Declaration of conformity

• DOCFE03004EN.pdf