



Product Code

FE03040

LOCK RELEASE MOD.410N-P22 MAX

Reference

3040

EAN

8424299030401

Description.

Description

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

Serie 410

This door lock release is made up of an electric mechanism MOD.410 which dimensions are:

52,5(V)x16,4(H)mm. Recommended for replacement. The smallest door lock on the market (front width 16,5mm). Installed in smaller aluminium or PVC frames. Includes radial latch allowing the bolt to rotate on its axis without having to make a lateral cut in the door frame, which is not possible in traditional latch-bolt locks. The standard version offers MAX adjustable latch, allowing the adjustment between the latch and the bolt in the installation proces.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

P22 type flush shield.

For access doors.

P22 type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release. Recommended for smaller-sized aluminium and PVC frames.

Dimensions: 22(H)x130(V) mm.

Technical Details

Consumption:

N, A 12Vac: 980mA

N-412 12Vdc: 400mA.

N-512 12Vdc: 200mA.

Details.

Weight (kg)

0.1865

Packaging measurements

(height x width x depth) cm

3,4x16,3x2,7

Video Door Entry system

Technologie

GENERICA